

# Outsulation® SMD System™ (formerly Sprint MD System®)

DS441

## Exterior Cladding With Moisture Drainage

---

### Stopping Moisture in its Tracks

For residential and light commercial construction, the Dryvit Outsulation SMD System offers outstanding insulating qualities and versatile beauty with an extra level of moisture protection. The drainage plane installed between the water-resistive barrier and the insulation board creates a drainage channel to weep incidental water to the exterior.



### Engineered for Moisture Drainage

The system's insulation board is mechanically fastened over a code-approved water-resistive barrier over plywood or OSB substrate with Dryvit's approved fasteners, which provide maximum wind load performance. The drainage plane creates a path, which allows for a quick exit of incidental moisture.

### A Transferable 10-Year Drainage and Materials Warranty--An Industry First

The Outsulation SMD System is backed by an unprecedented ten-year moisture drainage and materials warranty – an industry first. This unique assurance gives you an added level of confidence. The system is warranted to effectively drain any moisture that enters the wall between the insulation board and the water-resistive barrier. This innovative warranty also has another important benefit: it is transferable from the builder to the owner, and subsequent owners, during the covered ten-year period.

### Fast Installation, Perfect for Remodeling

The system's large dimension insulation board (4 ft x 8 ft) reduces the total number of joints and promotes faster and easier installation.

### Dryvit Energy Efficiency, Durability and Beauty

The Outsulation SMD System maintains the tradition of Dryvit's leadership in design flexibility, thermal efficiency (R-value 5.6 per inch thickness), impact resistance and superior finishes with proven resistance to dirt and mildew accumulation. All Dryvit finishes, in their wide variety of colors and textures, can be applied to the Outsulation SMD System. Dryvit finishes, as with all other exteriors, are designed to require normal maintenance (refer to Dryvit's Homeowner's Maintenance Guide, DS235, or the Cleaning and Recoating data sheet, DS152).

---

Dryvit Systems, Inc.  
One Energy Way  
P.O. Box 1014  
West Warwick, RI 02893  
800-556-7752  
www.dryvit.com

Printed in USA R4:01-13-09  
©Dryvit Systems, Inc. 1998

Information contained in this information page conforms to the standard detail recommendations and specifications for the installation of Dryvit Systems, Inc. products as of the date of publication of this document and is presented in good faith. Dryvit Systems, Inc. assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Dryvit Systems, Inc.

