

### Description

Weatherprime is a water-based, color-tinted acrylic primer, which provides a flat, non-slip uniformly absorbent, color-coordinated surface for application of Dryvit exterior Weatherlastic finishes. Weatherprime is available in a variety of standard colors as well as custom colors.

### Uses

Weatherprime is recommended for the surface preparation of stucco, concrete and masonry to color coordinate the substrate with the selected Dryvit Weatherlastic finish.

### Coverage

Approximately 1500 ft<sup>2</sup> (140 m<sup>2</sup>) per 50 lb (23 kg) pail, depending upon surface roughness and porosity of the substrate.

### Properties

**Drying Time** - The drying time of Weatherprime is dependent upon the air

temperature and relative humidity. Under average drying conditions [70 °F (21 °C), 55% R.H.], Weatherprime is dry to the touch in 1/2 hour and sufficiently dry for application of a Weatherlastic finish in 2 hours. Protect from rain for at least 4 hours.

### Application Procedure

**Job Conditions** - Air and surface temperature for application of Weatherprime must be 40 °F (4 °C) or higher and must remain so for a minimum of 24 hours.

### Temporary Protection -

Shall be provided at all times until all work is completed to protect the wall from weather and other damage.

### Surface Preparation -

Surfaces shall not be below 40 °F (4 °C) and must be clean, dry, structurally sound and free of efflorescence, grease, oil, form release agents and

curing compounds. On painted surfaces, remove all blistered or peeling paint to a sound substrate. Remove all gloss by sanding.

**Mixing** - Stir to a smooth, homogeneous consistency.

### Application -

Weatherprime can be applied using a brush, paint roller or spray equipment.

**Clean Up** - Clean tools with water while Weatherprime is still wet.

### Storage

Weatherprime must be stored at a minimum of 40 °F (4 °C) and a maximum of 100 °F (38 °C) in tightly sealed containers protected from weather and out of direct sunlight.

### Cautions and Limitations

- Avoid applying Weatherprime in direct sunlight. Always work on the shady side of the wall or protect the area with appropriate shading material.

**Technical and Field Service**  
Available on request.